

FARMAX 3-SERIES, 5-SERIES, 9-SERIES

Our most proud 3-series, 5-series, 9-series with reliable, easy operation, powerful and low fuel consumption make it a perfect model for farm jobs. Through our experience service teams provide full after sales support which satisfy the most demanding users.



3 SERIES

FARMAX 3354

35HP, 4X4



5 SERIES

FARMAX 5544

55HP, 4X4



9 SERIES

FARMAX 9540

90HP, 4X4

Sole Distributor

MENTAKAB AGRICULTURAL MACHINERY SDN. BHD. (624999-K)

No. 7, 8, 9, Jalan Industri 6, Taman Perindustrian Temerloh, 28400 Mentakab, Pahang, Malaysia.

Tel: 09-270 1818 / 019-932 3499 Fax: 09-270 1819 Website: www.mam.com.my Email: sales@mam.com.my

SPECIFICATION

TRACTOR MODEL		FARMAX 3354	FARMAX 5544	FARMAX 9540	
Drive Type		4WD	4WD	4WD	
ENGINE	Model	4T35	4T55	4T90	
	Power at rated speed (HP)	35	55	90	
	Max. rated speed (rpm)	2400	2400	2400	
	Type	Diesel, vertical, water cooled	Diesel, vertical, water cooled	Diesel, vertical, water cooled	
	No. of cylinders	4	4	4	
	Displacement (cc)	1532	4150	4950	
	Max. torque	≥ 135Nm@ 1700 - 1800rpm	≥ 248Nm@ 1500 - 1700 rpm	≥ 385Nm@ 1500 - 1700 rpm	
	Fuel consumption	≤ 230	≤ 220	≤ 210	
Air filter		Oil bath	Oil bath	Oil bath	
TRACTOR PARAMETER	Dimension	Length to front ballast(mm)	3306	3746	4458
		Width(mm)	1485	1685	2064
		Height to top of ROPS(mm)	1565	2565	2784
	Wheel track(min.)	Front(mm)	1205	1350	1800
		Rear(mm)	1400	1400	1600
	Wheel base(mm)		1600	2036	2330
	Ground clearance(mm)		335	350	395
	Gross weight(kg)		1450	2150	3300
	Min. turning radius	Without brake	3.1	4.3	5.15
		With brake	2.7	3.6	4.6
DRIVE TRAIN	Clutch		Dual-stage	Dual-stage	Dual-stage
	Number of speeds		4x(2+1)	4x(2+1)	(4+1)x2
	Steering		Power steering	Power steering	Power steering
	Brake		Wet disc	Wet disc	Wet disc
	Differential lock		Mechanical	Mechanical	Mechanical
	Standard tire size	Front	6.00-16	8.3-20	12.4-24
		Rear	11.2-24	14.9-24	18.4-30
PTO	Power(kW)	20.5	36.4	56.25	
	Speed(rpm)	540 & 1000	540 & 1000	540 & 1000	
HYDRAULIC SYSTEM	3 point lift capacity(kg)		900	1400	2500
	Working depth control		Draft, position control	Draft, position control	Draft, position control
	Category of 3 point link		CAT I	CAT II	CAT II
ELECTRICAL SYSTEM	Type		12V, Electric starter	12V, Electric starter	12V, Electric starter
CAPACITY	Fuel tank(l)		35	45	100
	Cooling system(l)		6.5	8	17
	Engine oil(l)		4.5	6	20

* ROPS as standard.

* Optional : Driving cabin (air-cond)
Synchro shuttle
Creeper gear
Turf tire, Industrial tire

* MAM-Implement is highly recommended.

* Specification and design of products may change without notice.

Authorised dealer: