

Farmax®

1 JENAMA 100 KEGUNAAN

The world's leading technology from European..... FARMAX

Our most proud 3-series, 5-series, 9-series with reliable, easy operation, powerful and low fuel consumption make it a perfect model for farm jobs and plantation. Through our experience service teams provide full after sales support which satisfy the most demanding users.

3 SERIES

FARMAX 3544

35HP, 4X4



9 SERIES

FARMAX 9044

90HP, 4X4



5 SERIES

FARMAX 5544

55HP, 4X4



Low Fuel
Consumption
Proven



O.E.C.D
Approval No. 410 980



ROSYAM NOR
DUTA / PENGEDAR FARMAX

Peserta Projek Pertanian Moden Lanchang,
Pahang, Malaysia.

				SPECIFICATION						
TRACTOR MODEL		FARMAX 3544		FARMAX 5544		FARMAX 9944				
Drive Type		4WD		4WD		4WD				
ENGINE	Model		4T35		4T55		4T90			
	Power at rated speed (HP)		35 (25.7KW)		55 (40.5KW)		90 (66.2KW)			
	Max. rated speed (rpm)		2400		2400		2400			
	Type		Diesel, vertical, water cooled		Diesel, vertical, water cooled		Diesel, vertical, water cooled			
	No. of cylinders		4		4		4			
	Displacement (cc)		1532		4150		4950			
	Max. torque		≥ 135Nm@ 1700 - 1800rpm		≥ 248Nm@ 1500 - 1700rpm		≥ 340Nm@ 1500 - 1700rpm			
	Fuel consumption		≤ 220		≤ 210		≤ 200			
Air filter		Oil bath		Oil bath		Oil bath				
TRACTOR PARAMETER	Dimension	Length to front ballast(mm)		3340		3780		4170		
		Width(mm)		1500		1750		2060		
		Height to top of ROPS(mm)		2320		2450		2800		
	Wheel track (min)		Front(mm)		1205		1350		1800	
			Rear(mm)		1400		1400		1600	
	Wheel base(mm)		1600		2036		2330			
	Ground clearance(mm)		335		350		395			
	Gross weight(kg)		1500		2150		3300			
	Min. turning radius		Without brake		3.1		4.3		5.15	
			With brake		2.7		3.6		4.6	
DRIVE TRAIN	Clutch		Dual-stage		Dual-stage		Dual-stage			
	Number of speeds		Synchro shuttle (8+8)		Synchro shuttle (8+8)		(5+1)x2			
	Steering		Power steering		Power steering		Power steering			
	Brake		Wet disc		Wet disc		Wet disc			
	Differential lock		Mechanical		Mechanical		Mechanical			
	Standard tire size		Front		6.50-16		8.3-20		12.4-24	
			Rear		12.4-24		14.9-24		18.4-30	
PTO		Power		29.8HP		52.4HP		80HP		
				(21.9KW)		(38.5KW)		(58.8KW)		
HYDRAULIC SYSTEM	3 point lift capacity(kg)		900		1400		2600			
	Working depth control		Draft, position control		Draft, position control		Draft, position control			
	Category of 3 point link		CAT I		CAT II		CAT II			
ELECTRICAL SYSTEM	Type		12V, Electric starter		12V, Electric starter		12V, Electric starter			
CAPACITY	Fuel tank(l)		35		45		100			
	Cooling system(l)		6.5		8		17			
	Engine oil(l)		4.5		6		20			

MENTAKAB AGRICULTURAL MACHINERY SDN. BHD. (624999-K)

No. 7, 8, Jalan Industri 6, Taman Perindustrian Temerloh,
28400 Mentakab, Pahang, Malaysia.

Tel : (+6) 09-270 1818 / (+6) 019-932 3499

Fax : (+6) 09-270 1819

Website : www.mam.com.my

Email : sales@mam.com.my

- * ROPS and canopy as standard.
- * Optional : Driving cabin (air-cond)
Synchro shuttle
Creeper gear
Turf tire, Industrial tire

- * Synchro shuttle on specific models.
- * MAM-Implement is highly recommended.
- * Specification and design of products may change without notice.

Authorised dealer: